



MARUI

PNEUMATIC FORKLIFT TYRES

- Specially developed tread compound for cooler running and wear resistance
- Wider tread profile for improved traction and stability
- Excellent long haul capabilities
- Reduces undercarriage repair
- Value for money
- Smooth driving
- High reliability





MARUI

PNEUMATIC FORKLIFT TYRES

MARUI : Conforms to ETRTO & TRA Standards

Pattern	Size	Ply Rating	Tread Depth (mm)	Standard Rim	Type	Out Side Diameter of New Tyre		Maximum Load (kg)	Maximum Pressure (kpa)	Maximum Pressure (lbs)
						Over all Diameter	Section Width			
HL903	5.00-8	10	11	3.50D	Tube Type	470	137	1295	900	130
	6.00-9	10	12	4.00E	Tube Type	540	160	1795	850	125
	6.00-9	12	12	4.00E	Tube Type	540	160	1970	1000	145
	6.50-10	10	12	5.00F	Tube Type	590	175	1965	775	110
	6.50-10	12	12	5.00F	Tube Type	590	175	2145	900	130
	7.00-9	10	9.5	4.33R	Tube Type	568	176	1300	700	100
	7.00-12	12	14	5.00S	Tube Type	676	190	2830	850	125
	8.25-12	12	15	5.00S	Tube Type	728	210	2000	700	100
	8.25-15	14	15	6.50	Tube Type	840	235	4435	800	115
	*28x9-15	14	16	7.00	Tube Type	710	220	3285	800	115

*28x9-15=8.15-15

Other sizes available on request.

Specifications are subject to change without notice.

TREAD PATTERN HL903



DISTRIBUTED BY :